

Our Ref.: 871-64
TT/13/US

U.S. PATENT APPLICATION

Inventor(s): Guy NATHAN

Invention: AUDIOVISUAL REPRODUCTION SYSTEM

***NIXON & VANDERHYE P.C.
ATTORNEYS AT LAW
1100 NORTH GLEBE ROAD
8TH FLOOR
ARLINGTON, VIRGINIA 22201-4714
(703) 816-4000
Facsimile (703) 816-4100***

SPECIFICATION

004240" 429T2960

AUDIOVISUAL REPRODUCTION SYSTEM

Field of the invention

This invention relates to a digital audiovisual reproduction system triggered by the payment of fees.

Background of the invention

5 International patent application WO 96/12257 deposited by the applicant relates to a system for a digital audiovisual reproduction system which will be described later. This system is also called a juke-box, and is usually placed in a leisure area such as a
10 bar. The bar manager who rents the audiovisual reproduction system from an operator can access functions for setting physical parameters, and also a management mode, through a touch screen and a graphic interface. He can use this screen and this interface
15 to order musical selections through an audiovisual data distribution network and a host server, and these musical selections will be downloaded onto the audiovisual reproduction system by a host server in the downloading center. The operator can also access
20 configuration functions for the reproduction system and can also order downloadable musical selections. Customers select songs using the touch screen

004220 27912250

associated with the graphic interface. This system is very efficient for the reproduction of sound and images, but it requires a certain amount of skill to set the physical parameters and requires frequent
5 movements by the operator. Furthermore, not all capabilities of the system are used.

Objects and summary of the invention

Therefore, the purpose of this invention is to
10 overcome the disadvantages of prior art by proposing an audiovisual reproduction system with many functions, particularly to enable increased interaction between the audiovisual reproduction system and the various user types, and to simplify its use.

15 The first purpose of this invention is to propose a function for controlling the volume of the sound output through the loudspeakers.

This purpose is achieved by the fact that the Audiovisual reproduction system comprising a central
20 unit managing a sound control circuit, and a telecommunications modem connected to a distribution network controlled by a host server, through a multitask operating system created around a library of tools and services, wherein the operating system
25 comprises a function that adjusts the sound control circuit to couple volumes in the various areas in which the loudspeakers in the audiovisual reproduction system are used, this function being accessible through a management mode of the multitask operating system, the
30 coupling maintaining the ratios between the various volumes in each area when the volume in one area is modified.

According to another feature, the volume generated by the loudspeakers is programmable using a tools and

004240 22960

services library management mode as a function of the time of the day.

According to another feature, the volume setting parameters can be downloaded through a request sent by the host server to the telecommunications modem in the audiovisual reproduction system.

A second purpose of this invention is to facilitate the work done by operators.

This second purpose is achieved by the fact that the audiovisual reproduction system comprises of a central unit controlling the display means, a touch screen, memory means and a telecommunications modem connected to a distribution network controlled by a host server through a multitask operating system comprising a library of tools and services, wherein the operating system of the reproduction system automatically sends a request to the host server requesting that at least one selected song be downloaded, each song being determined as a function of the answers to a questionnaire, which is stored in a file in the system memory means, to be displayed by display means at the appropriate moment, and to which users reply by actions on the touch screen.

According to another feature, the reproduction system or the operator download a list of songs on the host server through the information distribution network, the host server then downloading the songs in the list prepared by the operator into the memory means of a determined audiovisual reproduction system through the same distribution network.

According to another feature, an order is sent to at least one determined reproduction system through a file downloaded on the reproduction system through the host server, this order being memorized by the

004220" 22922960

A third purpose of this invention is to enable interaction between the user and the audiovisual reproduction system.

According to another feature, the display means show a screen that users of the audiovisual reproduction system can use through the telecommunications means to order entry tickets for the artistic events displayed on the display means, the payment for these entry tickets being made through payment means forming part of the audiovisual reproduction system.

30 According to another feature, the reproduction system comprises printing means for printing entry tickets or means of recording the entry tickets corresponding to artistic events shown on the display means, on a portable electronic object.

5

10

15

20

flexibility of use offered to the operator.

30

35

to select one song, the number of credits being stored in a file on the memory means, this file being updated each time that the manager uses a credit and each time that the operator supplies one or more credits.

5 According to another feature, credits supplied by the operator can be used within a given time range determined by a program module that displays a special screen for selection of time ranges within which the credits in the reserve may be used.

10 According to another feature, credit reserve can only be used by the manager, and is controlled by the manager entering a confidential code requested every time before the use of a credit in the reserve is validated.

15 According to another feature the operation consisting of crediting the credit reserve can only be used by the operator by entering a confidential code requested every time before adding a credit to the reserve is validated.

20 credits supplied by the operator can be used within a given time range.

25 According to another feature, the operator can limit the ranges of values within which the manager can modify the physical parameters of the audiovisual reproduction system.

Other features and advantages of this invention will become clearer after reading the following description with reference to the attached drawing.

30

Brief description of the drawing

35 - The sole shows an electrical diagram for an audiovisual reproduction system according to prior art compatible with the characteristics of the invention.

00621677-072400

Description of the preferred embodiments

Before beginning the actual description, it is worthwhile defining a number of elements. Firstly, the term "operator" is used in this description to describe a person or a company who installs and maintains the audiovisual reproduction system. The term "manager" is used to describe a person or a company who rents the audiovisual reproduction system, usually from an operator, and who uses the system for profit making purposes. Finally the term "user" is used to describe any person who uses the reproduction system rented by a manager for leisure purposes.

For example, the reproduction system used for
15 application of the characteristics of the invention is
as described in international patent application WO
96/12257 deposited by the applicant.

Preferably, but non-restrictively, the audiovisual reproduction system uses the hardware components listed and referenced below.

The central microprocessor unit (1) is a high performance PC compatible system, the choice at the time of the installation being made for an Intel type system which has at least the following memory means and characteristics:

- compatibility with the Vesa local bus
- processor cache memory: 256 kbytes
- 32 Mbyte of RAM
- high performance serial and parallel ports
- 30 - SVGA microprocessor type graphic adapter
- SCSI/2 type bus controller
- self-powered static RAM.

Another central unit with equivalent performances could be used in the invention.

00001677.072400

This central unit controls and manages a sound control circuit (5), a telecommunications control circuit (4), an input control circuit (3), a mass memory control circuit (2), and a display means control circuit (6). The display means comprise mainly of an SVGA type high resolution, low radiation, flat screen video monitor (62) without interlacing, this monitor being used for reproduction of images (for example album covers of musical selections), graphics and video clips.

The memory means also include storage modules (21) using high speed, high capacity, SCSI hard disks, and are associated with memory means already installed in the microprocessor device. These modules are used for the storage of audiovisual information.

A 28.8 kbps high speed telecommunications modem adapter (41) is included to enable the link to an audiovisual information distribution network controlled by a host server.

For reproduction of sound information for musical selections, the system comprises loudspeakers (54) receiving the signal from an amplifier-tuner (53) connected to the music synthesizer type of electronic circuit (5) designed to support a large number of input sources while providing an output with a CD (compact disk) type of quality, for example such as a "Sound Blaster" multimedia audio adapter card for use with a microprocessor

A 240 watt ventilated power supply with temperature control provides energy to the system. This power supply is protected against overvoltages and over oscillations.

The audiovisual reproduction system manages a touch screen (33) through its input controller circuit (3) which includes a glass coating panel using the

5
10

15

- 15

20

25

30

35

- the microphone on/off control,
 - the loudspeakers mute control,
 - the sound volume control,
 - a control canceling the musical selection
- 5 currently being played.

10 The system operating software is built up around a library of tools and services specifically oriented towards audiovisual applications in a multimedia universe. This library advantageously includes a high performance multitask operating system that efficiently enables simultaneous execution of multiple code fragments. This operating system thus enables concurrent execution of operations carried out on the display means, sound reproduction means and the

15 management of telecommunications links through the distribution network, in an orderly manner while avoiding any conflicts. This software is also very flexible.

20 Digitized and compressed audiovisual data are stored in the memory means (21).

Each selection is available in two digitized formats, with hi-fi quality or CD quality.

25 It is essential to note that although all modules described later are apparently used sequentially, in fact the tasks specific to these modules are executed simultaneously in an environment using the multitask operating system.

30 The first module, called the SSM module, is the system start module. This module only supplies a single service, and consequently it is automatically loaded when the system is switched on. If the system is started with a correct registration number, it then directly enters the "in service" mode of the RMM module.

00621677.072400

5

10

- 30

handed over to the IRM (inactivity routine module) for processing.

The system remains in "in service" mode until one of the events described above occurs.

5 The IRM module is the inactivity routines module. This module contains routines performing predetermined functions such as displaying the cover of an album, playing parts of musical tracks present in the system, reproduction of complete selections for internal
10 promotional purposes, audio reproductions for external promotional purposes, spoken promotional announcements of new musical selections, fallback to an auxiliary source that may be used when the system is inactive and after a predetermined but adjustable time period has
15 elapsed, corresponding to a time out.

The SMM module is the system management module. This module carries out functions that order the system to accept input requested through a infrared remote control device, these functions being processed
20 immediately without stopping the process that is taking place. A very large number of functions of this type is possible, and some possible functions are listed in the following non-restrictive list:

- 25 - adjustment of the sound volume of played selections,
- adjustment of the sound volume of the played auxiliary source,
- switching the microphone on/off,
- adjusting the microphone sound volume,
- 30 - balance adjustment, right channel, left channel,
- control of low frequency volumes,
- control of high frequency volumes,
- order to cancel or skip a range in a musical selection,
- 35 - order for panoramic effects, zoom in, zoom out,

09021677 "072400

- trigger reinitialization of the software program.

00420" 292360

The MMM module is the management mode module. This module is triggered when the manager turns the key switch. The ordinary screen display is replaced by a display specific to system management. With this new display, the manager is able to control all settings that can be made with the remote control. He can input additional low level commands, for instance to define commands to be enabled or disabled on the remote control. He can also define a maximum number of high and low levels for each system output source, these limits defining the range available on the remote control. The manager can use this screen to access new selection acquisitions mode by touching a button marked on the touch screen. When the manager has finished defining these commands and the system configuration, he simply removes the key and the system automatically returns to "in service" mode.

The NSAM module is the new selection acquisitions mode module.

The CBSM module is the customer browse and select mode module. This module is accessed from "in service" mode when the customer touches the screen. The user can display a menu that he can use for extensive browsing assisted by digitized voice messages to guide him in his choice of musical selections.

The TSM module is the telecommunications services mode module between the host server and the audiovisual reproduction system. This module is used to manage all management services available on the distribution network. All tasks specific to telecommunications are managed as system background tasks. These tasks never use more than a proportion of the processing time remaining after the system has completed all its foreground tasks. Thus when the system is busy with

5 The SSC module is the system security control
module. This module manages system security, each
system gets into contact with a local controller system
according to a predetermined time scheme for
acquisition of the approval signal in the form of the
0 registration number which enables it to operate.
Furthermore, the said system automatically stops
operating if a fraud is observed or if the system can
no longer communicate to the network.

Finally, the manager uses the remote control to manage the system through the SMM module.

According to the invention, the volume settings in the various areas may be coupled if management mode is activated. This particular procedure is included in the MMM management module and is materialized on the touch screen (33) by a specific display comprising a button. The coupling procedure is activated when the manager or the operator touches this button. The first operation carried out by this function is to read values of the sound volumes in the different areas from a file stored on the reproduction system memory means, and the ratios between these various values will be calculated. These ratios are stored in a file stored on the reproduction system memory means (21). When the

volume of a determined area is subsequently modified, the procedure automatically reads the new value of the volume in the determined area and calculates the values of the volumes for the other areas such that the ratios
5 between the values for the various areas are identical to the previously calculated and stored ratios. When the coupling procedure is activated, and when the maximum value of the sound volume in one of the areas is reached, increasing the volume in any other area
10 will have no effect. The coupling function is deactivated either by touching the activation button again, or by touching another button, identified as deactivation button on the touch screen.

Advantageously, in order to avoid repeated
15 manipulations to modify the volume, volume modifications are stored in a file so that the volume in different areas can be reduced or increased at determined times. For example (1), this function performed by a routine in the reproduction system
20 operating system, is very useful when the reproduction system is located (1) in a bar. The background noise due to the presence of customers varies at different times of the day. This background noise is higher in busy periods, in other words usually during the
25 evening, and is low when there are fewer people. This situation requires that the sound volume of the reproduction system should be adapted as a function of the background noise. Thus according to the invention, the volume level can be programmed in advance as a
30 function of the time of the day. The routine in the operating system of the audiovisual reproduction system reads this file later, thus automatically making the preprogrammed changes to the volume level.

Advantageously, the file containing the volume
35 settings as a function of the time of the day can be

09621677 "072400

downloaded onto the memory means of the audiovisual reproduction system through the data distribution network and the reproduction system modem (41), in other words there is no need to be able to access reproduction system in order to create this file. The file may be generated on a different computer system and then downloaded onto the reproduction system through the distribution network and the telecommunications modem (41).

10 Audiovisual reproduction systems according to prior art enable downloading of new selections through a distribution network and a host server. However, commands for new selections must be made through the touch screen (33) and a module in the operating system of each reproduction system, and in some cases requires operator intervention. In order to avoid repeated movements of the operator to order new selections, the operating system has a procedure integrated into a module of the reproduction system by which the user can choose at least one new selection in a list. This procedure consists of starting to read the file stored on the memory means which displays a special screen on the display means (62). This screen contains a window in which a list of songs is displayed in the form of a popup menu. This list corresponds to selections that are not yet available on the audiovisual reproduction system, but which could be downloaded on the reproduction system. Thus, a message is displayed on the screen inviting users to select the new song(s) that they would like to have on the audiovisual reproduction system simply by touching the touch screen (33) on the title of the required song. Users' choices are memorized in a file stored on the memory means, which is updated whenever a user chooses a new selection in the list. The number of times that a

09621677.072400

example, this feature may be used to promote a new album or a concert given by a singer. For example, this feature could be used to play the title song of a singer's new album on all reproduction systems, on the day that it is distributed in the shops. This feature can also be used to distribute a song by this singer on reproduction systems located close to the location at which a concert given by the singer will shortly be held. Playing a particular song at a particular moment on at least one particular reproduction system is initiated by a series of orders contained in a file located on each audiovisual reproduction system. The orders contained in the file determine which song should be played and the moment(s) at which it should be played. Advantageously, the file containing orders for execution of the particular song at a particular moment is downloaded on each reproduction system concerned through the host server and the distribution network. The orders contained in the file will be executed when the audiovisual reproduction system reads this file.

The reproduction system according to the invention can also be used to create an interaction with the user. This interaction is materialized by a series of functions. The first function consists of using display means (62) to show at least one image and/or animation related to a coming artistic event close to the reproduction system. This display informs the users about this event. These sequences of images and/or animations are memorized in a file stored on the memory means of the reproduction system. The images and/or animations will be displayed when this file is read, for example through the IRM module (inactivity routines management module). Advantageously, a user can use the reproduction system according to the

09621577-072400

invention to order entry tickets for the artistic event described by the images and/or animations displayed on the display means of the reproduction system. A special button is displayed on the screen displaying the images and/or animations of the artistic event, for this purpose. If a user touches this button, a subroutine starts which will display a new screen. The user can use this new screen to order tickets for the artistic event. For example, the screen may have different possible booking dates, the type of seats available, the means of payment preferred by the user and any other information necessary to prepare the entry ticket. Advantageously, the payment means (35) in the audiovisual reproduction system are used for payment of the entry tickets. Advantageously the audiovisual reproduction system comprises means that firstly enable communication with the host server or the rental server and secondly, after receiving agreement, are capable of printing entry tickets. The means of issuing entry tickets also or alternatively comprise means of recording the entry ticket on a portable electronic object, such as a smart card. For example, these means may include means of reading from and writing to the electronic circuit of a smart card. When a user would like to book an entry ticket, a screen invites him to insert his card in the reading and writing means. This action triggers a procedure in the operating system of the reproduction system which firstly triggers a new card user identification procedure and secondly (after the entry tickets rental server has approved) triggers steps to record the entry ticket on the card electronic circuit. The file memorizing images and/or animations describing the artistic event may advantageously be downloaded on at

09621677-072400

least one audiovisual reproduction system through the host server and the distribution network.

Another feature of the reproduction system according to the invention is to make a request to users by means of at least one image stored in a file and displayed by display means (62) of the audiovisual reproduction system by executing a procedure in the operating system of the audiovisual reproduction system. The procedure is triggered whenever a particular event occurs. The image comprises a series of windows. For example, a first window may include a series of questions about the user, for example his or her age, sex, profession and/or any other information. A second window may for example include a series of questions about the required inquiry. For example this inquiry may be a satisfaction inquiry about a particular artist, or any other inquiry. Each question is associated with a particular answer area on the touch screen (33). The answers to the various questions are made simply by touching this area. Answers to the various questions in the inquiry are memorized in a file stored on the memory means of the audiovisual reproduction system. This file is then downloaded onto the host server. Advantageously, a subroutine in the operating system verifies if the questionnaire corresponding to the inquiry was fully filled in by the user. If so, the operating system triggers a subroutine that will credit means (35) of payment of an amount corresponding to one song selection and informs the user that he has the right to select an additional song, by displaying a special screen. Advantageously, the procedure to display the screen containing the series of questions is triggered by a predetermined event. For example, this event may be the selection of a particular song or the n(th)

004220" 22972960

selection of the same or a different song by the same user, which corresponds to a determined payment amount.

Advantageously, the display means (62) of the reproduction system are used to display advertisements.

5 Advertising displays are triggered by a subroutine in the operating system, for example after the user has made a given number of paying musical selections. This advertisement, memorized in a file stored on the memory means, appears in the form of a game designed around
10 the company being advertised. Interaction between the user and the game forming the interactive advertising consists of the user pressing on the touch screen (33) of the reproduction system. If the user wins the game, a subroutine in the operating system of the
15 reproduction system is triggered to either credit payment means (35) by an amount corresponding to the selection of a song and inform the user on a specific screen that he has the right to make a musical selection of his choice free of charge, or to display a
20 special screen inviting the user to answer a questionnaire. For example, the questionnaire may be an inquiry about satisfaction with the audiovisual reproduction system or any other inquiry of the type described above.

25 The reproduction system according to the invention also provides the operator with a certain degree of flexibility. With the audiovisual reproduction system according to the invention, the operator can pay the manager of the reproduction system for a particular
30 number of credits. A credit is equal to the fee necessary to select one song. This credit reserve is stored in a file stored on the memory means (21) of the reproduction system. To add one credit to the reserve, the operator accesses a first specific button, using a
35 specific screen. Touching the touch screen (33) at the

004220" 22972950

position of this button triggers a subroutine in the reproduction system which updates the file corresponding to the credit reserve and adds one credit to this reserve. When the manager wants to use a credit in the reserve, he uses a second special screen to access a second special button. Touching the touch screen (33) at the location of this second button triggers a subroutine in the operating system which firstly credits the payment means (35) of the reproduction system by an amount corresponding to payment of the price to select one song, if the credit reserve is not empty, and secondly updates the file corresponding to the credit reserve by removing one credit from the reserve. The use of credits is reserved exclusively for the manager, who uses them by inputting a code required when the second special button is used or by means of a special function on the remote control means (31). Access to the credit reserve file is reserved exclusively to the operator (for example by means of a code requested when the first special button is used). Thus, the operator alone can increase the credit reserve, and the manager alone can use this reserve. Advantageously, there is a program module for displaying a special screen to define time periods during which credits offered by the operator can be used. A subroutine prevents access to the second special button outside these determined time ranges, so that the manager cannot use credits in the reserve.

In order to prevent the manager from incorrectly using management mode functions of the audiovisual reproduction system, the operator may fix ranges of values between which the manager can modify the physical settings of the audiovisual reproduction system. These limitations are made by means of low

09621677 072400

level functions exclusively accessible in MMM mode (Module management mode) by a special screen that is locked, for example, by means of a code known only to the operator. Due to these limitations, there is no
5 risk that the manager will make the reproduction system completely inoperative, and the operator will need to make fewer interventions.

It is obvious that other modifications that can be made by an expert in the subject fall within the scope
10 of the invention.

0000220" 44972950